

# GROUNDING PRODUCTS

## GROUND RODS

### Copper Bonded Ground Rods

Manufactured from high tensile low carbon steel by molecularly bonding 99.9% pure electrolytic copper. These ground rods are UL-467 listed and have a minimum copper thickness of 10 mils.



Copper Bonded Ground Rods			
Catalog #	Rod Dia	Length	Copper Thickness
38-4635-06	1/2"	8'	10 mils
38-4635-01	5/8"	8'	10 mils
38-4635-00	5/8"	10'	10 mils
38-4635-03	3/4"	8'	10 mils
38-4635-04	3/4"	10'	10 mils

### Sectional Copper Bonded Ground Rods

Manufactured from high tensile low carbon steel by molecularly bonding 99.9% pure electrolytic copper. These ground rods are UL-467 listed and have a minimum copper thickness of 10 mils. The rods are threaded by rolling threading process.



Copper Bonded Ground Rods				
Catalog #	Rod Dia (in)	Length (ft)	Thread Dia	Copper Thickness
38-4635-71	5/8"	8'	5/8"	10 mils
38-4635-21	5/8"	10'	5/8"	10 mils
38-4635-23	3/4"	8'	3/4"	10 mils
38-4635-24	3/4"	10'	3/4"	10 mils